

CARTRIDGE TYPE FOAM



Model: FE 6C, FE 9C

Application

- Cartridge type foam fire extinguisher, suitable for A & B fire classes such as ordinary combustible materials and flammable liquids.
- Reliable components are carefully chosen to give maximum efficiency along with high quality agent, to achieve high performance.
- Bristol extinguishers designed and manufactured in compliance with BS 5423 & BS/EN3 3.1&3.3

Features

- Seamless deep drawn container made of high tensile cold rolled sheet.
- Minimal welding points to give attractive appearance.
- Polyester resin electrostatically coated to give high quality weather resistance.
- Quality silk-screen printing with operating instruction.
- High bursting pressure.
- Epoxy resin electrostatically internal coating to give high quality against corrosion.
- 3% AFFF Hydral foam or 6% AFFF Hydral foam can be used.
- Quality machined and chrome plated brass safety vale with EPDM "O" ring.
- Built in pressure relief mechanism.
- Controlled discharge operation.
- Quality pressure gauge with EPDM "O" rings.
- Ease of maintenance and refilling.
- Durable components and least spare parts consumption.
- Meets or exceeds BS requirements.
- Simple operation and maintenance.
- Squeeze grip, positive on-off operation.
- Brass chrome-plated valve.
- Carbon steel shell with protective inner liner & corrosion resistant.
- Easy service construction
- Available in 6 & 9 Liters.

Description

Bristol Foam Extinguisher can be utilized in many Class A hazards such as office environments and industrial locations, as well as warehouse and oxidizing chemical storage areas.

Agent

Foam

Standard Portable sizes

6 Ltr. & 9 Ltr.

Packing

Single piece cardboard boxes

FIRE EXTINGUISHER



Technical Data

Model Specification	FE 6C	FE 9C
Fire Class	AB	
Extinguishing Agent	Foam AFFF Hydral	
Capacity (KG)	6	9
Discharge Time (sec)	45	85
Operating Temp Range(°C)	From 0 °C to + 60 °C	
Propelling gas	Nitrogen	
Test Data (bar)	12 – 15 bar	
Working Pressure	25 to 30 bar	
Dimensions and Weights		
Overall height (mm)	510	545
Certification	BUREAU VERITAS	
Certificate Reference No.	DBA 4.99.445/11	