

# MOBILE FOAM – CARTRIDGE TYPE



## Model: MFE 10C, MFE 20C, MFE 35C

### Application

- Cartridge type mobile foam fire extinguisher, suitable for A & B fire classes such as ordinary combustible materials and flammable liquids.
- Reliable components are carefully chosen to give maximum efficiency along with high quality agent, to achieve high performance.
- Bristol extinguishers designed and manufactured in compliance with BS 5423 & BS/EN3 3.1 & 3.3.

### Features

- Polyester resin electrostatically coated to give high quality as before.
- Trolley Nozzle with pistol type for ON and OFF.
- Quality machined and chrome plated brass safety valve with EPDM "O" ring.
- Built in pressure relief mechanism.
- Controlled discharge operation.
- Quality external CO<sub>2</sub> / N<sub>2</sub> Cartridge.
- Ease of maintenance and refilling.
- Durable components and least spare parts consumption.
- 1 year limited warranty.
- Two wheels as a standard.
- Available with 3 wheels.

### Specification

See Technical Data overleaf.

### Standard Portable sizes

10 Gal., 20 Gal., & 35 Gal.

### Packing

Single piece cardboard boxes.

# FIRE EXTINGUISHER



## Technical Data

Model Specification	MFE 10C	MFE 20C	MFE 35C
Fire Class	AB		
Extinguishing Agent	Foam AFFF Hydral		
Capacity (KG)	10	20	35
Discharge Time (sec)	85	35	150
Operating Temp Range(°C)	From 0 °C to + 60 °C		
Test Data (bar)	12 – 15 bar		
Working Pressure	25 to 30 bar		
Test pressure	25 to 30 bar		
Dimensions and Weights			
Overall height (mm)	1020	1370	1410