## MOBILE FOAM – PRESSURIZED





### **Model: MFE 10, MFE 20, MFE 35**

#### **Application**

- Pressure type mobile foam fire extinguisher, suitable for A&B fire classes such as ordinary combustible materials and flammable liquids.
- Reliable components are carefully chosen to give maximum efficiency along with high quality agent to achieve high performance
- Bristol extinguishers designed and manufactured in compliance with BS 5423 & BS/EN3 3.1&3.3.

#### **Features**

- Polyester resin electrostatically coated to give high quality weather resistance.
- High bursting pressure.
- Epoxy resin electrostatically internal coating to give high quality against corrosion.
- 3% AFFF Hydral foam or 6% AFFF Hydral foam can be used.
- Quality machined and chrome plated safety valve with EPDM "O" ring.
- Built in pressure relief mechanism.
- Controlled discharge operation with pistol nozzle.
- Quality Pressure gauge with EPDM "O" rings.
- Ease of maintenance and refilling.
- Durable components and least spare parts consumption.
- 1 year limited warranty.
- Two wheels as standard
- Available with 3 wheels.

#### **Specification**

See Technical Data overleaf.

#### **Standard Portable sizes**

10 Gal, 20 Gal & 35 Gal.

#### **Packing**

Single piece cardboard boxes.

# FIRE EXTINGUISHER



#### **Technical Data**

Model Specification	MFE 10	MFE 20	MFE 35	
Fire Class	AB			
Extinguishing Agent	Foam AFFF Hydral			
Capacity (KG)	10	20	35	
Discharge Time (sec)	85	35	150	
Operating Temp Range(°C)	From 0 °C to + 60 °C			
Test Data (bar) Working Pressure	12 – 15 bar			
Test pressure		25 to 30 bar		
Dimensions and Weights Overall height (mm)	1020	1370	1410	





