

MOBILE PRESSURIZED WATER



Model: MWE 10, MWE 20, MWE 35

Application

- Pressure Type mobile water fire extinguisher, suitable for A fire class such as ordinary combustible materials.
- Reliable components are carefully chosen to give maximum efficiency along with high quality agent, to achieve high performance.
- Bristol Extinguishers designed and manufactured in compliance with BS5423 & BS/EN3 3.1 & 3.3

Features

- Polyester resin electrostatically coated to give high quality weather resistance.
- High bursting pressure.
- Epoxy resin electrostatically internal coating to give high quality against corrosion.
- Quality machined and chrome plated brass safety valve with EPDM "O" ring
- Built in pressure relief mechanism.
- Controlled discharge operation with pistol nozzle.
- Quality Pressure gauge with EPDM "O" rings.
- Ease of maintenance and refilling.
- Durable components and least spare parts consumption.
- Two wheels as standard
- Available with 3 wheels.

Standard Portable sizes

10 Ltr., 20 Ltr. & 35 Ltr.

Packing

Single piece cardboard boxes

FIRE EXTINGUISHER



Technical Data

Model Specification	MWE 10	MWE 20	MWE 35
Fire Class	A		
Extinguishing Agent	Water		
Capacity (KG)	10	20	35
Discharge Time (sec)	85	135	150
Operating Temp Range(°C)	From -20°C to +60°C		
Propelling gas	Nitrogen		
Test Data (bar)	12 to 15 bar		
Working Pressure	25 to 30 bar		
Test pressure	25 to 30 bar		
Dimensions and Weights			
Overall height (mm)	1020	1370	1410