

# PRESSURIZED FOAM



## Model: FE 6, FE 9

### Application

- Pressure type foam fire extinguisher, suitable for A & B fire classes such as ordinary combustible materials and flammable liquids.
- Reliable components are carefully chosen to give maximum efficiency along with high quality agent, to achieve high performance.
- Bristol extinguishers designed and manufactured in compliance with BS 5423 & BS/EN3 3.1 & 3.3.

### Features

- Seamless deep drawn container made of high tensile cold rolled sheet.
- Minimal welding points to give attractive appearance.
- Polyester resin electrostatically coated to give high quality weather resistance.
- Quality silk-screen printing with operating instruction.
- High bursting pressure.
- Epoxy resin electrostatically internal coating to give high quality against corrosion.
- 3% AFFF Hydral foam or 6% AFFF Hydral foam can be used.
- Quality machined and chrome plated brass safety vale with EPDM "O" ring.
- Built in pressure relief mechanism.
- Controlled discharge operation.
- Quality pressure gauge with EPDM "O" rings.
- Ease of maintenance and refilling.
- Durable components and least spare parts consumption.
- Meets or exceeds BS requirements.
- Simple operation and maintenance.
- Squeeze grip, positive on-off operation.
- Brass chrome-plated valve.
- Carbon steel shell with protective inner liner & corrosion resistant.
- Easy service construction
- Available in 6 & 9 Liters.

### Description

Bristol Foam Extinguisher can be utilized in many Class A hazards such as office environments and industrial locations, as well as warehouse and oxidizing chemical storage areas.

### Agent

Foam

### Standard Portable sizes

6 Ltr. & 9 Ltr.

### Packing

Single piece cardboard boxes



## Technical Data

Model	FE6	FE9	FE6	FE9
Capacity (Kg)	6	9	6	9
Cylinder Diameter (mm)	160	180	161	175
Cylinder Height (mm)	470	525	510	600
Cylinder Volume (l)	8	11.30	8	11.3
Cylinder weight (Kg)	3.30	4.60	2.60	4.00
Fire Rating	21A, 144B, C	21A, 183B, C		
Extinguisher Weight (Kg)	10	14	9.60	14.00
Packing Size (L-W-H) (mm)	170x180x580	190x100x640	170x200x540	220x220x550
Working Pressure (Bar)	18		12 to 15	
Test Pressure (Bar)	27		25 to 30	
Operation Temperature	0 °C to + 60 °C			