

PRESSURIZED WATER



Model: WE 6, WE 9

Application

- Pressure type water fire extinguisher, suitable for A fire classes such as ordinary combustible materials.
- Reliable components are carefully chosen to give maximum efficiency along with high quality agent, to achieve high performance.
- Bristol extinguishers designed and manufactured in compliance with BS 5423 & BS/EN3 3.1 & 3.3.

Features

- Seamless deep drawn container made of high tensile cold rolled sheet.
- Minimal welding points to give attractive appearance.
- Polyester resin electrostatically coated to give high quality weather resistance.
- High bursting pressure.
- Epoxy resin electrostatically internal coating to give high quality against corrosion.
- Quality silk-screen printing with operating instruction.
- Quality machined and chrome plated brass valve with EPDM "O" ring.
- Built in pressure relief mechanism.
- Controlled discharge operation.
- Quality pressure gauge with EPDM "O" rings.
- Ease of maintenance and refilling.
- Durable components and least spare parts consumption.
- Meets or exceeds BS requirements.
- Simple operation and maintenance.
- Squeeze grip, positive on-off operation.
- Brass chrome plated valve.
- Carbon Steel Shell with protective inner liner & corrosion resistant.
- Easy service construction.
- Available in 6 & 9 Liters.

Description

Bristol Stainless Steel Water Extinguisher can be utilized in many Class A hazards such as office environments and industrial locations, as well as warehouse and oxidizing chemical storage areas.

Specification

See Technical Data overleaf.

Standard Portable sizes

6 Ltr. & 9 Ltr.

Packing

Single piece cardboard boxes

FIRE EXTINGUISHER



Technical Data

Model Specification	WE 6	WE 9
Fire Class	A	
Extinguishing Agent	Water	
Capacity (KG)	6	9
Discharge Time (sec)	40	49
Operating Temp Range(°C)	From 0 °C to + 60 °C	
Test Data (bar)	12 to 15 bar	
Working Pressure	25 to 30 bar	
Test pressure	25 to 30 bar	
Dimensions and Weights		
Overall height (mm)	510	545
Certification	DBA 4.99.445/12	
BUREAU VERITAS		
Certificate Reference No.		

Kitemark approved

Model	WE 6	WE 9
Capacity (Kg)	6	9
Cylinder Diameter (mm)	160	175
Cylinder Height (mm)	497	600
Cylinder Volume (l)	3.5	4.8
Cylinder weight (Kg)	39.77	52.97
Fire Rating	8A	13A
Extinguisher Weight (Kg)	10	14.3
Packing Size (L-W-H) (mm)	185x200x630	185x200x710
Working Pressure (Bar)	13	
Test Pressure (Bar)	25	
Operation Temperature	-5 °C to + 60 °C	