

ZR451-3

Wireless 868 MHz Single Input/Output Interface Unit

General

The ZR451-3 is a wireless, 868 MHz single channel input/output unit. It provides a method of interfacing a supervised input or potential free output signal into and out of the fire detection and alarm system in areas where the installation of system wiring is not an option.

Usage

As an input the ZR451-3 may receive signals from other alarm equipment, e.g. beam detectors, aspiration detectors etc. Used as an output the unit switches equipment controlled by the fire detection system, e.g. air conditioning systems, magnetic door release units etc. Both input and output facilities are available from the same unit and may be operated simultaneously or individually, as programmed at the fire control panel.

The system

The ZR451-3 communicates with the main control panel via a hardwired, radio loop module that can be installed anywhere on the ZP loop. When the input gets an alarm signal it passes it via the radio loop module to the main fire control panel where it is processed. The output of the interface provides volt free change over contacts for connecting ancillary equipment and is programmed separately, activated individually or in a group.

High intensity LED indicators positioned on the ZR451-3 may be illuminated by a manually activated push button to identify when the interface has operated, providing clear identification of the signal source.

Installed as part of a ZP addressable system, up to 127 line devices (sensors, call points or interface units) may be connected to each of the control panel loops. Each wireless device is assigned its own IDENT address with which the main control panel communicates with it, providing the same system facilities as directly wired devices.



Standard Features

- Addressable input/output interface unit
- Wire free activation
- Volt free relay output
- Monitored input for fire and fault
- Two way radio communication

ZR451-3

Wireless 868 MHz Single Input/Output Interface Unit

Specifications

Model No	ZR451-3
Description	Radio Input/Output Unit complete with battery pack
Compatibility	All ZP systems via ZPR868 radio loop module
Mounting	Surface
Approval	CPD certified to EN54:18, and EN54:25 ENTSI 300-220
Monitoring	Continuously self-checking
Indications	6 LEDs illuminated by push switch operation
Power supply	6 x Duracell AA MN1500 LR6 alkaline batteries
Output	Volt free contact, rated 2A@24VDC
Application	Indoor installation
EN60529 rating	IP42
Temperature range	-10°C to +70°C
Humidity range (noncondensing)	10% to 95% RH
Material	Moulded ABS
Dimensions (w x h x d)	240 x 120 x 50 mm
Colour	Cool grey
Weight	600g

Power supply

The ZR451-3 is powered by an 6 Duracell AA MN1500 LR6 alkaline batteries providing up to 5 years of operational life under normal site conditions. The ZR451-3 features battery condition monitoring and reporting.

Ordering Information

Part No.	Description
ZR451-3	Wireless 868 MHz Single Input/Output Interface Unit